

PRODUCT BULLETIN

Q-Vent Tip Vent Window Ventilator



greenteQ

Q-Vent Tip Vent Window Ventilator

Q-Vent Tip Vent is a frame mounted plastic window ventilator.

It is available from stock in 2000, 3000 and 4000mm² free area sizes, providing 1400, 2500 and 2700mm² equivalent area respectively.

Tip Vents are supplied as a set (internal vent and external hood complete with insect grille) in seven attractive colours (see list overleaf). Dual Colour sets are also available from stock. Bespoke colours are available to special order.

The internal vent features a positive open and close action, whilst the 4000 version offers a dual opening inner, providing 2 airflow options. Airflow is always deflected upwards on all sizes.

Standard Q-Vent Tip Vents are screw fix but a clip fix option is available to special order on some versions.

VBH Item Codes and slot routing details can be found overleaf.

Specifications

- Air Permeability (tested to BS EN 13141-1): 50Pa-3.9l/s (closed position)
- Water Tightness (tested to BS EN 13141-1): No leakage @ 600 Pa
- Acoustics (tested to BS EN ISO 717-1:1999 & BS EN ISO 10140-2 2011)
Under normal circumstances the vent achieved the following results:
Open - up to 32 Dne W
Closed - up to 37 Dne W

Benefits at a glance

- 1400, 2500 & 2700mm² equivalent area sizes
- Supplied complete in a set
- Can be fitted to sash, frame or overhead through an add-on profile
- 7 standard colours with bespoke colours and mixed colours available
- Manufactured from sturdy UV-stabilised plastic
- Positive open and close action with split opening on 2700 version
- Upward air deflection
- Modern design






Q-Vent Tip Vent Window Ventilator

VBH Order Codes

Description	2000/1400 mm ²	3000/2500 mm ²	4000/2700 mm ²
White	5QSV0001	5QSV0021	5QSV0041
Black	5QSV0003	5QSV0023	5QSV0043
Anthracite Grey (RAL7016)	5QSV0006	5QSV0026	5QSV0046
Light Grey (RAL7040)	5QSV0008	5QSV0028	5QSV0048
Brown (RAL8017)	5QSV0004	5QSV0024	5QSV0044
Oak (RAL8003)	5QSV0005	5QSV0025	5QSV0045
Cream (RAL9001)	5QSV0002	5QSV0022	5QSV0042
Chartwell Green	5QSV0007	5QSV0027	5QSV0047
White In/Black Out	5QSV0013	5QSV0033	5QSV0053
White In/ Anthracite Grey Out	5QSV0016	5QSV0036	5QSV0056
White In/Light Grey Out	5QSV0018	5QSV0038	5QSV00582
White in/ Brown Out	5QSV0014	5QSV0034	5QSV0054
White In/ Oak Out	5QSV0015	5QSV0035	5QSV0055
White In/Cream Out	5QSV0012	5QSV0032	5QSV0052
White In/Chartwell Green Out	5QSV0017	5QSV0037	5QSV0057

Routing Details

Airflow Guide

Geometric Open Area (mm ²)	Equivalent Area (mm ²)	Slot Height (mm)	Overall Slot Length (mm)	Fixing Method	Overall Vent Length (mm)	Overall Hood Length (mm)
4000	2700	12		Screw Fix Only	430	430
4000	2700	12		Screw and/or Clip Fix		
3000	2500	16		Screw Fix Only	315	315
3000	-	12		Screw and/or Clip Fix		
2000	1400	12		Screw and/or Clip Fix	249	249

Cross Section Dimensions

