

PRODUCT BULLETIN

greenteQ Safeguard Cable Window Restrictor



greenteQ Safeguard Window Restrictor

The Safeguard Window Restrictor from greenteQ is a simple yet very effective way of restricting the maximum opening angle of windows to prevent falls from height.

The strong 160mm cable links the sash and frame components together to restrict the opening. It is recommended to fit the sash and frame units side by side but if these components are offset this will reduce the permitted opening.

There are two variants to choose from; the 'Key to Release' version can be disengaged by turning a key to release one end of the cable, while the 'Tamper Resistant' option is permanently fixed in place. It can be released using a screwdriver when it is necessary to open the window fully (for maintenance reasons, for example).

Both options are available in black and white finishes and both are suitable for fixing to inward and outward opening windows of all materials. They are supplied with self-drilling screws for aluminium, steel and reinforced PVCu profiles. If the restrictor is to be fitted to another material, the appropriate fixings should be sourced separately.

The 'Key to Release' variant requires a 2-handed operation to disengage the restrictor.

Benefits at a glance:

- Simple means of preventing falls and otherwise restricting inward and outward opening windows
- 'Key to Release' with 2-handed operation, and 'Tamper Resistant' options
- White and black options to match/complement all profile colours
- Meets the requirements of BS EN 13126-5:2011 and BS EN 14351-1:2006

Safeguard Window Restrictor

greenteQ

VBH Order Codes

VBH Code	Description	Box Qty
2QMA0131	White 'Key to Release' Restrictor	50
2QMA0132	Black 'Key to Release' Restrictor	50
2QMA0135	White Tamper Resistant Restrictor	50
2QMA0136	Black Tamper Resistant Restrictor	50